

02/23/99
Jc639 U.S. PTO

A

+

Please type a plus sign (+) inside this box → ☐ +
Approved for use through 09/30/2000. OMB 0651-0032
Patent and Trademark Office: U.S. DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

**UTILITY
PATENT APPLICATION
TRANSMITTAL**

(Only for new nonprovisional applications under 37 C.F.R. § 1.53(b))

Attorney Docket No.	1630
First Inventor or Application Identifier	PARUPUDI et al.
Title	System Event Notification Service
Express Mail Label No.	EE506162915US

APPLICATION ELEMENTS

See MPEP chapter 600 concerning utility patent application contents.

1. ☒ * Fee Transmittal Form (e.g., PTO/SB/17)
(Submit an original and a duplicate for fee processing)
2. ☒ Specification [Total Pages **50**]
(preferred arrangement set forth below)
 - Descriptive title of the invention
 - Cross References to Related Applications
 - Statement Regarding Fed sponsored R & D
 - Reference to Microfiche Appendix
 - Background of the invention
 - Brief Summary of the invention
 - Brief Description of the Drawings (if filed)
 - Detailed Description
 - Claim(s)
 - Abstract of the Disclosure
3. ☒ Drawing(s) (35 U.S.C. 113) [Total Sheets **8**]
4. Oath or Declaration [Total Pages **2**]
 - a. ☒ Newly executed (original or copy)
 - b. ☐ Copy from a prior application (37 C.F.R. § 1.63(d))
(for continuation/divisional with Box 16 completed)
 - i. ☐ **DELETION OF INVENTOR(S)**
Signed statement attached deleting inventor(s) named in the prior application, see 37 C.F.R. §§ 1.63(d)(2) and 1.33(b).

*** NOTE FOR ITEMS 1 & 13: IN ORDER TO BE ENTITLED TO PAY SMALL ENTITY FEES, A SMALL ENTITY STATEMENT IS REQUIRED (37 C.F.R. § 1.27), EXCEPT IF ONE FILED IN A PRIOR APPLICATION IS RELIED UPON (37 C.F.R. § 1.28).**

ADDRESS TO:

Assistant Commissioner for Patents
Box Patent Application
Washington, DC 20231

PTO
Jc552/60
U.S. 155614

02/23/99

5. ☐ Microfiche Computer Program (Appendix)
6. Nucleotide and/or Amino Acid Sequence Submission (if applicable, all necessary)
 - a. ☐ Computer Readable Copy
 - b. ☐ Paper Copy (identical to computer copy)
 - c. ☐ Statement verifying identity of above copies

ACCOMPANYING APPLICATION PARTS

7. ☒ Assignment Papers (cover sheet & document(s))
8. ☐ 37 C.F.R. § 3.73(b) Statement (when there is an assignee) ☒ Power of Attorney
9. ☐ English Translation Document (if applicable)
10. ☐ Information Disclosure Statement (IDS)/PTO-1449 ☐ Copies of IDS Citations
11. ☐ Preliminary Amendment
12. ☒ Return Receipt Postcard (MPEP 503)
(Should be specifically itemized)
13. ☐ * Small Entity Statement(s) filed in prior application, Status still proper and desired (PTO/SB/09-12) ☐ Statement filed in prior application, Status still proper and desired
14. ☐ Certified Copy of Priority Document(s) (if foreign priority is claimed)
15. ☐ Other: _____

16. If a CONTINUING APPLICATION, check appropriate box, and supply the requisite information below and in a preliminary amendment:

<input type="checkbox"/> Continuation	<input type="checkbox"/> Divisional	<input type="checkbox"/> Continuation-in-part (CIP)	of prior application No: _____
Prior application information: Examiner _____		Group / Art Unit: _____	

For CONTINUATION or DIVISIONAL APPS only: The entire disclosure of the prior application, from which an oath or declaration is supplied under Box 4b, is considered a part of the disclosure of the accompanying continuation or divisional application and is hereby incorporated by reference. The incorporation can only be relied upon when a portion has been inadvertently omitted from the submitted application parts.

17. CORRESPONDENCE ADDRESS

<input type="checkbox"/> Customer Number or Bar Code Label	(Insert Customer No. or Attach bar code label here)	or <input checked="" type="checkbox"/> Correspondence address below
--	---	---

Name	Albert S. Michalik, Reg. No. 37,395				
	The Law Offices of Albert S. Michalik				
Address	704 - 228th Avenue NE				
	Suite 193				
City	Redmond	State	Washington	Zip Code	98053
Country	USA	Telephone	(425) 836-3030	Fax	(425) 836-3003

Name (Print/Type)	Albert S. Michalik	Registration No. (Attorney/Agent)	37,395
Signature	<i>Albert S. Michalik</i>	Date	2/23/99

Burden Hour Statement: This form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Box Patent Application, Washington, DC 20231.

+

In re Application of PARUPUDI et al.
Attorney Docket No. 1630

CERTIFICATE OF MAILING BY "EXPRESS MAIL"

"Express Mail" mailing label number EE506162915US

Date of Deposit: February 23, 1999

I hereby certify that the following documents:

New Patent Application in the name of Gopal Parupudi, Mario C. Goertzel and Murthy Srinivas for "System Event Notification Service," including 1 Page Cover Sheet, 38 Pages Specification, 10 Pages Claims, 1 Pages Abstract, 8 Sheets Of Drawings, Transmittal Sheet, Fee Transmittal Sheet, Executed Declaration and Power of Attorney, Assignment Recordation Cover Sheet and Assignment

are being deposited with the United States Postal Service "Express Mail Post Office To Addressee" Service under 37 C.F.R. 1.10 on the date indicated above and is addressed to: Assistant Commissioner for Patents, Washington, D.C. 20231.

Sonja A. Michalik

(Typed or printed name of person mailing paper or fee)

(Signature of person mailing paper or fee)

S P E C I F I C A T I O N

TO ALL WHOM IT MAY CONCERN:

Be it known that we, Gopal Parupudi, a citizen of India residing at 4221 255th Place SE, Issaquah Washington 98029, Mario C. Goertzel, a citizen of the United States, residing at 12631 NE 107th Place, Kirkland, Washington 98033, and Murthy Srinivas, a citizen of the United States residing at 9611 213th Avenue NE, Redmond, Washington 98053, have invented a certain new and useful SYSTEM EVENT NOTIFICATION SERVICE of which the following is a specification.

SYSTEM EVENT NOTIFICATION SERVICE

TECHNICAL FIELD

The invention relates generally to computer systems, and
5 more particularly to an improved method and mechanism for
providing computer application programs with computer system
events, including network events.

BACKGROUND OF THE INVENTION

10 At times, application programs need or could benefit from
certain system event information. By way of example, an
application program that deals with a network may need to
determine if the network is available to that program, i.e.,
whether the computer system is connected to the network and
15 the network is operational. Another application program, such
as a word processing program, may benefit from knowing if the
state of battery charge was getting critically low, whereby
the application program could automatically save a copy of any
open files.

20 To the extent that such system information may be
obtained, the mechanisms for obtaining the information are
independent within the various applications. For example,
each application that deals with the network essentially
implements its own technology to determine the state of

network connectivity. Such technology uses often crude and incomplete heuristics for this purpose.

Moreover, because many system events such as battery low conditions and network disconnects can happen at any time, some regular calling or polling mechanism is generally needed to detect such conditions. However, such polling consumes resources, which is particularly wasteful since the result is usually unchanged. At the same time, individual polling is redundant. For example, if some system facility (such as an application programming interface, or API) reports the charge of the battery, a word processor, spreadsheet and another application each may be configured to separately and regularly poll the facility to determine the charge.

Particular problems arise with mobile computing, since in mobile computing environments, users often change the state of network connectivity. At the same time, local area network (LAN) connectivity is particularly difficult to detect, since there is not any uniform way to determine the state of LAN connectivity, e.g., LAN cards do not adequately provide the needed connectivity information. Simply monitoring for activity is not sufficient, since even if there is activity on a LAN interface, such activity may be only broadcast / loopback activity, and not indicative of real network connectivity. In short, applications heretofore have not had

an integrated model for obtaining computer system event information, including network connectivity and other information.

5

SUMMARY OF THE INVENTION

10 Briefly, the present invention provides a method and system for providing system event notifications to clients such as applications. Clients register for notification of one or more types of events with a registration mechanism, and a System Event Notification Service, (SENS), receives system event information and fires events in response thereto. A distribution mechanism selectively communicates the fired event to each client registered for notification thereof based on the type of event. SENS preferably uses the Loosely
15 Coupled Events database to match client subscribers interested in the information SENS is capable of publishing.

20 For network events, the System Event Notification Service monitors the connectivity state of the machine. SENS provides the connectivity state information via an application programming interface (API) or by sending notifications to subscribers via the distribution mechanism. The information may include whether the connection is established or lost, the type of connection (LAN / WAN) and bandwidth information. SENS also provides information on other system events,

including logon or logoff operations and power management, and may be extended to provide other types of system event information such as notifications of plug and play operations.

To monitor a LAN state, SENS caches outgoing and
5 incoming network information including errors and packet counts. SENS evaluates this cached information against current information to determine whether the connection is available or not and additionally to determine if a connection was established or lost. SENS also evaluates the WAN state if
10 RAS (Remote Access Services) is installed. SENS further determines if a destination (IP address or name) is reachable, by periodically polling destinations, preferably via system threadpool timers. To monitor events such as logon/logoff or power management, SENS registers with the operating system.
15 SENS may also interface with one or more other clients to delay logging off until the other client or clients can complete certain work.

Other advantages will become apparent from the following detailed description when taken in conjunction with the
20 drawings, in which:

BRIEF DESCRIPTION OF THE DRAWINGS

FIGURE 1 is a block diagram representing a computer system into which the present invention may be incorporated;

FIG. 2 is a block diagram representing general components for distributing system events to registered clients in accordance with one aspect of the present invention;

FIG. 3 is a block diagram representing a centralized service and mechanism for firing event notifications, and interfaces in a client registered for notifications, in accordance with one aspect of the present invention;

FIG. 4 is a block diagram representing sources for triggering a network connectivity state evaluation and components therefor in accordance with one aspect of the present invention;

FIG. 5 is a representation of a cache for maintaining local area network information to evaluate the network connectivity state in accordance with one aspect of the present invention;

FIG. 6 is a flow diagram generally representing the steps taken to evaluate the connectivity state of a local area network and for firing corresponding network system events in accordance with one aspect of the present invention;

FIG. 7 is a flow diagram generally representing the steps taken to determine whether a specified network destination is reachable and for firing corresponding network system events in accordance with one aspect of the present invention;

FIG. 8 is a representation of a cache for periodically polling network destinations to determine the reachability thereof; and

FIG. 9 is a representation of a thread pooling arrangement useful for periodically polling network destinations to determine the reachability thereof.

DETAILED DESCRIPTION OF THE INVENTION

Exemplary Operating Environment

FIGURE 1 and the following discussion are intended to provide a brief general description of a suitable computing environment in which the invention may be implemented. Although not required, the invention will be described in the general context of computer-executable instructions, such as program modules, being executed by a personal computer. Generally, program modules include routines, programs, objects, components, data structures and the like that perform particular tasks or implement particular abstract data types. Moreover, those skilled in the art will appreciate that the invention may be practiced with other computer system configurations, including hand-held devices, multi-processor systems, microprocessor-based or programmable consumer electronics, network PCs, minicomputers, mainframe computers and the like. The invention may also be practiced in

distributed computing environments where tasks are performed by remote processing devices that are linked through a communications network. In a distributed computing environment, program modules may be located in both local and remote memory storage devices.

With reference to FIG. 1, an exemplary system for implementing the invention includes a general purpose computing device in the form of a conventional personal computer 20 or the like, including a processing unit 21, a system memory 22, and a system bus 23 that couples various system components including the system memory to the processing unit 21. The system bus 23 may be any of several types of bus structures including a memory bus or memory controller, a peripheral bus, and a local bus using any of a variety of bus architectures. The system memory includes read-only memory (ROM) 24 and random access memory (RAM) 25. A basic input/output system 26 (BIOS), containing the basic routines that help to transfer information between elements within the personal computer 20, such as during start-up, is stored in ROM 24. The personal computer 20 may further include a hard disk drive 27 for reading from and writing to a hard disk, not shown, a magnetic disk drive 28 for reading from or writing to a removable magnetic disk 29, and an optical disk drive 30 for reading from or writing to a

removable optical disk 31 such as a CD-ROM or other optical media. The hard disk drive 27, magnetic disk drive 28, and optical disk drive 30 are connected to the system bus 23 by a hard disk drive interface 32, a magnetic disk drive interface 33, and an optical drive interface 34, respectively. The drives and their associated computer-readable media provide non-volatile storage of computer readable instructions, data structures, program modules and other data for the personal computer 20. Although the exemplary environment described herein employs a hard disk, a removable magnetic disk 29 and a removable optical disk 31, it should be appreciated by those skilled in the art that other types of computer readable media which can store data that is accessible by a computer, such as magnetic cassettes, flash memory cards, digital video disks, Bernoulli cartridges, random access memories (RAMs), read-only memories (ROMs) and the like may also be used in the exemplary operating environment.

A number of program modules may be stored on the hard disk, magnetic disk 29, optical disk 31, ROM 24 or RAM 25, including an operating system 35 (preferably Windows® 2000), one or more application programs 36, other program modules 37 and program data 38. A user may enter commands and information into the personal computer 20 through input devices such as a keyboard 40 and pointing device 42. Other

input devices (not shown) may include a microphone, joystick, game pad, satellite dish, scanner or the like. These and other input devices are often connected to the processing unit 21 through a serial port interface 46 that is coupled to the system bus, but may be connected by other interfaces, such as a parallel port, game port or universal serial bus (USB). A monitor 47 or other type of display device is also connected to the system bus 23 via an interface, such as a video adapter 48. In addition to the monitor 47, personal computers typically include other peripheral output devices (not shown), such as speakers and printers.

The personal computer 20 may operate in a networked environment using logical connections to one or more remote computers, such as a remote computer 49. The remote computer 49 may be another personal computer, a server, a router, a network PC, a peer device or other common network node, and typically includes many or all of the elements described above relative to the personal computer 20, although only a memory storage device 50 has been illustrated in FIG. 1. The logical connections depicted in FIG. 1 include a local area network (LAN) 51 and a wide area network (WAN) 52. Such networking environments are commonplace in offices, enterprise-wide computer networks, Intranets and the Internet.

When used in a LAN networking environment, the personal computer 20 is connected to the local network 51 through a network interface or adapter 53. When used in a WAN networking environment, the personal computer 20 typically includes a modem 54 or other means for establishing communications over the wide area network 52, such as the Internet. The modem 54, which may be internal or external, is connected to the system bus 23 via the serial port interface 46. In a networked environment, program modules depicted relative to the personal computer 20, or portions thereof, may be stored in the remote memory storage device. It will be appreciated that the network connections shown are exemplary and other means of establishing a communications link between the computers may be used.

EVENT NOTIFICATION

Turning now to FIG. 2, the System Event Notification Service 60 (SENS) is a centralized mechanism which publishes notifications to appropriate clients $62_1 - 62_n$. Clients are subscribers that essentially subscribe via a registration mechanism 64 for events in which they are interested. When the SENS 60 receives system event information corresponding to an event for which a client is registered, the SENS 60 fires an event to a distribution mechanism, preferably embodied in a

COM object referred to as an event class object 66, which in turn publishes the event to only those client subscribers 62₁ - 62_n that are registered for that event. A filtering mechanism 68 may also be included as part of the event class object 66 or connected thereto, whereby certain events are filtered out based on client-specified conditions (i.e., parameters) that may be associated with an event. For example, the client can register for a notification of when the computer system is on battery power, but further specify that notification should only occur if the battery charge is at or below twenty percent. The filtering mechanism stops the fired event notification from reaching that client unless the battery charge is below the specified twenty percent level.

Although not necessary to the present invention, the registration mechanism 64, distribution mechanism (event class object) 66 and filtering mechanism 68 used by the SENS 60 are preferably incorporated into a COM+ events database-like technology generally referred to herein as the Loosely Coupled Events database 70. The Loosely Coupled Events database 70 and associated filtering mechanism 68 are described in more detail in copending United States patent applications, entitled "Object Connectivity Through Loosely Coupled Publish And Subscribe Events," and "Object Connectivity Through Loosely Coupled Publish And Subscribe Events With Filtering,"

respectively, both assigned to the assignee of the present invention, filed concurrently herewith, and hereby incorporated by reference herein in their entireties. These applications will hereinafter be referred to as the
5 aforementioned "Loosely Coupled Events" applications.

Thus, aspects of the present invention are herein described with reference to the Loosely Coupled Events model, which is incorporated into an object services component of Microsoft Corporation's Windows® 2000 (server) operating
10 system. In general, the Windows® 2000 operating system is a scaleable, high-performance network and computer operating system supporting distributed client / server computing, and provides an object execution environment for component applications, including those conforming to the component
15 object model (COM). COM is described in detail in "*Inside OLE, Second Edition*", Kraig Brockschmidt, Microsoft Press (1995). The COM+ component incorporates object services that implement the illustrated publish and subscribe event communication model. As used herein, "COM" is used to refer
20 to the object model defined in the Microsoft Component Object Model, whereas "COM+" refers to the system services, system-provided objects and system-defined interfaces of the COM+ object services component of Microsoft Windows® 2000. Notwithstanding, there is no intention to limit the present

invention to the Windows® 2000 operating system, COM and/or COM+, but on the contrary, the present invention is intended to operate with and provide benefits with any mechanism that fires and distributes event notifications in response to receiving system information. For example, the present invention has also been implemented in Microsoft® Corporation's Internet Explorer 5.0 for Windows NT 4.0 and Windows® 95 and Windows® 98 operating systems.

The Loosely Coupled Events database 70 includes information about the event publisher (i.e., SENS), event subscribers, and filters. During setup, when Microsoft® Windows 2000® is installed or upgrades another operating system, the SENS 60 adds itself as a publisher to a COM+ Events data store, and provides information on the classes of events that it monitors using a GUID for each class of events.

In the Loosely Coupled Events model, the SENS 60 is a publisher that fires events to the distribution mechanism, the aforementioned COM object referred to as the event class object 66. More particularly, the SENS 60 calls a method of an interface (e.g., 72₂) of the event class object 66, which in turn handles the work of publishing the event to the client subscribers 62₁ - 62_n registered for the event. For purposes of simplicity herein, calling a method of a COM object will not be described in detail, since such an operation is well

documented. The work performed by the event class object 66 includes retrieving subscription information, creating the client subscriber (object) if not running, and multi-casting the event via method calls to the individual subscribers.

5 More particularly, the event class object 66 (distribution mechanism) calls methods or APIs of the registration mechanism 64 (e.g., COM+ Events subscription retrieval / enumeration APIs) when an event is "fired" by the SENS 60, so as to pass the event to the appropriate
10 subscribers to the event. Note that the interfaces $72_1 - 72_m$ of the event class object 66 are ordinarily defined by the developer of the SENS 60 publisher to handle the events fired thereby. Note further that the Loosely Coupled Events
15 database 70 communicates with the SENS 60 so that certain types of events are not fired unless at least one client has registered for that type of event, since firing events can be costly in terms of consuming system resources.

The SENS 60 is an event publisher for the classes of events that it monitors, including network, logon, and power /
20 battery events, and the client application program receiving a notification is called an event subscriber, as described below. While the SENS 60 is primarily for local system events, the distributed component object model (DCOM) enables the SENS 60 to be extended to network clients.

The client subscribers $62_1 - 62_n$ are also COM Objects in the Loosely Coupled Events model, each of which may have a subscription to a method or methods of the interface 72_2 . Application programs typically create a sink object (FIG. 3) to receive appropriate notifications. The subscriptions cause the event class object 66 of the Loosely Coupled Events database 70 to propagate events fired on the methods to the subscribers, shown in FIG. 2 as $62_1 - 62_2$, but not 62_n . To this end, the client subscribers $62_1 - 62_2$ individually expose one or more interfaces, shown in FIG. 2 as the interfaces $74_1 - 74_n$. Each such interface is essentially defined identically to one of the interfaces $72_1 - 72_m$. The event class object 66 propagates the event by calling the method of each of the subscriber's interfaces (e.g., 74_1 and 74_2) that corresponds to the method called by the publisher in that event class object's interface (e.g., 72_2).

Note that an application (e.g., its sink object receiving the notification) does not have to be active (running) when the notification is sent. When an application subscribes to receive notifications, the application may specify whether it should be activated when the event occurs or notified later when it is active. The subscription can be transient and valid only until the application stops running, or it can be

persistent and valid until the application is removed from the system.

To selectively associate clients with events, the Loosely Coupled Events database 70 includes subscription objects 76₁ - 76_j. Each object (e.g. 76₂) associates a particular subscriber (e.g., client 62₁) and a particular method of an event interface (e.g. 72₂) of a particular event class object, (e.g., the event class object / SENS distribution mechanism 66). To create the subscription / association, the registration mechanism 64 includes COM+ services in the form of methods or APIs that can be called to register, remove or modify subscriptions, (as well as to retrieve or enumerate subscriptions to a particular outgoing-event interface method). More particularly, each client subscribes to the SENS events that interest it via IEventSubscription and IEventSystem interfaces in the COM+ Events registration mechanism 64. An identifier for the event classes is supplied, along with the SENS publisher identifier, SENSGUID_PUBLISHER. Subscriptions are on a per-event level, whereby the subscribing application also specifies which events within the class are of interest thereto. As described above, each event corresponds to a method in the interface corresponding to its event class.

66E220" +399260
The client subscriber objects 62₁ - 62_n may implement the
code that calls the method or API of the registration
mechanism 64 for registering a subscription, so as to
subscribe to a particular interface method. Alternatively,
5 other programs may use the subscription registration method or
API of the registration mechanism 64 to enter a subscription
for a subscriber object. Accordingly, the clients 62₁ - 62_n
need not include code to register a subscription. Instead,
subscriptions can be entered for the client subscriber object
10 (e.g., 62₂) by other programs. For example, an installation
program that is run at installation of the subscriber object
on the computer system 20 may enter a subscription, as may
other component programs of an application that incorporates
the subscriber object. Similarly, an administration utility
15 such as "Microsoft Management Console," may configure
subscriptions for the subscriber object. Additional details
on publishers, the event class object, subscribers, and
subscriptions are set forth in the aforementioned "Loosely
Coupled Events" patent applications.

20 Thus, the SENS 60 enables applications to receive
notifications from system events that SENS 60 monitors. When
the requested event occurs, the SENS 60 notifies the
application. At present, the SENS 60 can notify applications
about three classes of system events, including TCP/IP network

events, such as the status of a TCP/IP network connection or the quality of the connection, user logon events, and battery and AC (alternating current) power events.

An application can subscribe to multiple system events, such as establishment of network connectivity, notification when a specified destination can be reached within specified Quality of Connection (QOC) parameters, and when the computer has switched to battery power. The application can also subscribed to be notified when the percentage of remaining battery power is within a specified parameter, or when other scheduled events occur.

In accordance with one aspect of the present invention, one way in which a client (e.g., application) can determine network connectivity information is via application programming interfaces to the SENS 60, IsNetworkAlive() and IsDestinationReachable(). The IsNetworkAlive() function determines whether the local system is connected to a network and the type of network connection, for example, LAN, WAN, or both. The IsDestinationReachable() function determines if the specified destination can be reached, and provides Quality of Connection (QOC) information for the destination. Additional details are set forth below:

```

Bool IsNetworkAlive(
    LPDWORD lpdwFlags    // Specifies the type of network connection
);

```

5

Parameters

lpdwFlags

Provides information on the type of network connection available when the return value is TRUE. The flags can be:

10 NETWORK_ALIVE_LAN

the computer has one or more LAN cards that are active.

NETWORK_ALIVE_WAN

the computer has one or more active RAS connections.

15 Return Values

TRUE

The local system is connected to a network.

FALSE

Call **GetLastError** to determine the reason for no connectivity.

20

Remarks

This function is used by applications that want to know whether there is network connectivity before proceeding with network operations. Applications such as directory service applications, e-mail clients, or Internet browsers can adapt to various kinds of network connectivity. For example, a printing operation can be deferred until the network connection is available. Note that at present, this function is only available for TCP/IP connections.

30

Bool IsDestinationReachable(

 LPCSTR lpszDesination, // Pointer to string specifying destination

 LPQOCINFO lpQOCInfo // Pointer to Quality of Connection information

35

);

Parameters

lpszDestination

Pointer to a string that specifies the destination. The destination can be an IP address, a UNC name, or an URL.

40

lpQOCInfo

Pointer to the QOCINFO structure that receives the Quality of Connection (QOC) information. You can supply a NULL pointer if the QOC information is not desired.

5

Return Values

TRUE

The destination can be reached.

FALSE

10 Call **GetLastError** to determine the reason why the destination cannot be reached.

Remarks

15 This function is used by client applications to determine the QOC information before proceeding with network operations. For standalone computers that are directly connected to the network through a network card or remote access server (RAS), this function generates minimal network traffic with RPC calls to the nearest router. For computers that are part of a network where the
20 destination can be reached using RAS or a network gateway, this function pings to the destination to generate accurate QOC information. Note that at present, this function is only available for TCP/IP connections.

25 The caller supplies the buffer for the QOCINFO structure and must release this memory when it is no longer needed.

30 The **QOCINFO** structure is returned by the **IsDestinationReachable** function and provides Quality of Connection information to the caller.

typedef struct tagQOCINFO {
 DWORD dwSize;
 DWORD dwFlags;
35 DWORD dwInSpeed;
 DWORD dwOutSpeed;
} QOCINFO, *LPQOCINFO;

Members

dwSize

Upon calling the IsDestinationReachable function, the caller supplies the size of the QOC structure in this member. On return from the function, this member contains the actual size of the structure that was filled in.

dwFlags

Speed of connection. Flag bits indicate whether the connection is slow, medium, fast.

dwInSpeed

Speed of data coming in from the destination in bytes per second.

dwOutSpeed

Speed of data sent to the destination in bytes per second.

In accordance with another aspect of the present invention, another way in which a client (e.g., application) receives system events is by subscribing a sink object 80 or the like for notifications of events that interest it. As shown in FIG. 3, the subscriber application creates a sink object 80 with an implementation for each interface that it handles. The various types of events are generally categorized into appropriate interfaces, i.e., network-type events in one interface, power-type events in another interface, logon-type events in another interface and so on.

FIG. 3 shows such a client subscriber sink object 80 set up to receive a relatively large number of SENS events, including network-type events via an ISensNetwork interface, power-type events via an ISensOnNow interface and logon-type events via an ISensLogon interface. Also, plug-and-play type events may be handled by the SENS 60, and although not presently

implemented, are shown herein to illustrate the extensibility of the present invention by simply adding additional interfaces such as ISensPnP with appropriate methods. Of course, a typical sink object ordinarily will not implement this many events, however FIG. 3 illustrates many of the possible events. The SENS 60 predefines an outgoing interface for each event class in a type library, as set forth in Table 1 below:

Table 1

Event Class	GUID	Interface
Network events	SENSGUID_EVENTCLASS_NETWORK	ISensNetwork
Logon events	SENSGUID_EVENTCLASS_LOGON	ISensLogon
Power events	SENSGUID_EVENTCLASS_ONNOW	ISensOnNow

The SENS 60 defines the SENS coclass as part of the SENS type library. The SENS object implementation is provided by the operating system, as set forth in Tables 2 and 3 below.

Table 2 - Creation/Access Functions

CoCreateInstance	Creates an instance of the SENS object using its CLSID.
-------------------------	---

Table 3 - Interfaces

ISensNetwork	Default. Outgoing interface implemented by sink object in subscriber application.
ISensOnNow	Outgoing interface implemented by sink object in subscriber application.
ISensLogon	Outgoing interface implemented by sink object in subscriber application.

The ISensNetwork interface handles network events fired by the SENS 60. Each event corresponds to a method in the

ISensNetwork interface, an outgoing interface defined by the SENS 60 and implemented by the subscriber application as a dispatch interface. The following table, Table 4, sets forth the methods of the ISensNetwork interface that correspond to

5 network events:

Table 4

ISensNetwork Methods	Description
ConnectionMade	Specified connection has been established.
ConnectionMadeNoQOCInfo	Specified connection has been established with no Quality of Connection information available.
ConnectionLost	Specified connection has been dropped.
DestinationReachable	Specified connection can be reached.
DestinationReachableNoQOCInfo	Specified connection can be reached with no Quality of Connection information.

10 Additional details on some of the methods of the ISensNetwork interface are set forth below:

```

ISensNetwork::ConnectionMade
The specified connection has been established.
15 HRESULT ConnectionMade(
    BSTR bstrConnection,    // Connection name
    ULONG ulType,           // Connection type
    LPSENS_QOCINFO lpQOCInfo // Pointer to Quality of Connection
                             // information
20 );

```

Parameters

bstrConnection

[in] The name of the connection. For WAN connections, the connection name is the name of the phone book entry; for LAN connections, it is the name of the network card.

ulType

[in] Connection type. This value can be CONNECTION_LAN or CONNECTION_WAN.

lpQOCInfo

[out] Pointer to the SENS_QOCINFO structure which contains Quality of Connection information.

5 Dispatch Identifier
[id(0x00000001)]

Return Values

S_OK

10 Method returned successfully.

Remarks - SENS calls this method to notify an application that the specified connection has been established. SENS also provides a pointer to a structure containing Quality of Connection information.

15 Note that at present, this function is only available for TCP/IP connections.

20 SENS_QOCINFO Structure

The SENS_QOCINFO structure is provided by the ISensNetwork::ConnectionMade method and the ISensNetwork::DestinationReachable method. This structure contains Quality of Connection information to the sink object in an application that subscribes to the System Event Notification Service (SENS).

25 typedef struct _SENS_QOCINFO {
30 DWORD dwSize;
 DWORD dwFlags;
 DWORD dwOutSpeed;
 DWORD dwInSpeed;
 } SENS_QOCINFO;

35 Members

dwSize

This member contains the actual size of the structure that was filled in.

dwFlags

40 Speed of connection. Flag bits indicate whether the connection is slow, medium, fast.

dwOutSpeed

Speed of data sent to the destination in bits per second.

45 dwInSpeed Speed of data coming in from the destination in bits per second.

ISensNetwork::DestinationReachable

Directed to whether a specified connection can be reached.

HRESULT DestinationReachable(

```
5   BSTR bstrDesination,      // Destination name
    BSTR bstrConnection      // Connection name
    ULONG ultype              // Connection type
    LPSENS_QOCINFO lpQOCInfo  // Quality of Connection information
);
```

10 Parameters

bstrDestination

[in] Name of the destination. The name may be an IP address, a URL, a UNC, or a NetBIOS name.

15 *bstrConnection*

[in] Name of the connection. For WAN connections, the connection name is the name of the phone book entry; for LAN connections, it is the name of the network card.

20 *ulType*

[in] Connection type. This value can be CONNECTION_LAN or CONNECTION_WAN.

lpQOCInfo

25 [out] Pointer to the SENS_QOCINFO structure which contains Quality of Connection information.

Dispatch Identifier

[id(0x00000004)]

30

Return Values

S_OK

Method returned successfully.

35 Remarks

SENS calls this method to notify an application that the specified destination can be reached. A pointer to a structure containing Quality of Connection information is also provided.

40 Note that at present, this function is only available for TCP/IP connections.

ISensNetwork::DestinationReachableNoQOCInfo

45 The specified connection can be reached with no Quality of Connection information.

HRESULT DestinationReachableNoQOCInfo(

```
50   BSTR bstrDesination,      // Destination name
    BSTR bstrConnection,      // Connection name
    ULONG ultype              // Connection type
);
```

Parameters

bstrDestination

[in] The name of the destination. Can be an IP address, a URL, a UNC, or a NetBIOS name.

bstrConnection

[in] Name of the connection. For WAN connections, the connection name is the name of the phone book entry; for LAN connections, it is the name of the network card.

ulType

[in] Connection type. This value can be CONNECTION_LAN or CONNECTION_WAN.

Dispatch Identifier

[id(0x00000005)]

Return Values

S_OK

Method returned successfully.

Remarks

SENS calls this method to notify an application that the specified destination can be reached when Quality of Connection information is not available.

Note that at present, this function is only available for TCP/IP connections.

Several types of applications, for example, can utilize the connectivity functions and notification services that the SENS 60 offers. These include an application that requires network connectivity status, such as an application that utilizes directory services, or an application that adapts its operations depending on the level of connectivity and the quality of network services, such as an Internet browser that functions at a reduced level on a low bandwidth connection. Other applications that may benefit from this information include an application that can perform deferred operations,

such as an electronic mail program that can queue messages while offline and send them when a connection is established.

Connectivity functions and notifications are also useful for certain computer configurations, such as a mobile computer
5 used in a docking station on a high bandwidth network which may occasionally use a dial-in connection, a mobile computer using a dial-in connection exclusively, a desktop computer using a dial-in connection exclusively or a desktop computer connected to a high bandwidth network with latency issues. In
10 each of these configurations, the connection bandwidth and latency information can be used by an application to dynamically optimize its operations for network availability.

As described above, LAN cards in general do not provide the appropriate LAN connectivity information needed to
15 appropriately fire system events related thereto. However, in accordance with one aspect of the present invention, the SENS 60 provides a mechanism for detecting the network connectivity state, so that it can appropriately fire events in response to state changes. To this end, as shown in FIGS. 4 and 5, the
20 SENS 60 caches network information in time-based caches 82_{T0} and 82_{T2}. The cached information includes Unicast and non-Unicast incoming and outgoing network packet counts and incoming and outgoing error counts. These counts start at zero when the machine is last rebooted, and never decrease

(until the next reboot). For each interface, this information is maintained as part of a TCP/IP stack 84 and made accessible through Internet Protocol Help (IPHLP) APIs 86. As described below, a snapshot is taken of the network information at two
5 distinct times to fill the LAN caches 82_{T0} and 82_{T2}, and the differences in counts evaluated by an evaluation mechanism 88 within the SENS 60 to determine network connectivity, i.e., whether the network is alive (true) or not (false).

FIG. 6 shows the general process for determining network
10 connectivity, beginning at step 600. One way to trigger the steps of FIG. 6 is when an application program 90 (FIG. 4) or the like calls the above-described IsNetworkAlive() API 91, requesting the network connectivity state information. Also, the SENS 60 can periodically check the state (e.g., once every
15 two minutes) and appropriately fire events on state changes to registered clients. Certain other activities can also trigger the evaluation of network connectivity, as represented in FIG. 4 by ovals 92 - 95. These include plug and play events 92 directed to a LAN card, since plugging or unplugging such a
20 card is likely to change the state of network connectivity. Similarly, certain network user interface activity 93, wherein a user can specifically ask to change the network connectivity state, may trigger a reevaluation. Remote Access Services (RAS) events 94 and Media Sense activity 95 can also trigger a

reevaluation of network connectivity. Note that RAS may directly provide event information indicating whether a WAN connection is alive, which the SENS 60 then utilizes to fire events. Further, note that these other events essentially enter the reevaluation process at step 606, while the API call initially evaluates the last state by entering the process at step 600. Thus, when an API calls triggers the reevaluation, as an optimization, the network connectivity is not checked if it is alive (true) and has been checked recently, since networks do not fail often and evaluating the network information is relatively expensive. However, the network information is evaluated if false, or if one of the certain circumstances (described above) has taken place, since those events tend to happen when the network connectivity state changes, regardless of when last checked.

If during the IsNetworkAlive() API call the network state was last determined to be true, step 600 branches to step 602 to test if the time duration, i.e., the current time minus the previous time T_0 , presently selected in one embodiment at 180 seconds, has been achieved since the last time connectivity was evaluated. If the duration is less than a threshold time, i.e., $T_1 < T_0 + 180$, it is not yet time to check, whereby step 602 branches to step 604 where a "True" network state is returned. Alternatively, as shown in FIG. 6, if the network

state is "False" (step 600) or if the time to check has been achieved ($T_2 \geq T_0 + 180$) at step 602, step 606 is next executed to fill a time-based cache 82_{T2} with network information at the current time, T_2 . Note that the first time, (since reboot), the state is assumed to be false, whereby an evaluation of the network information will take place.

As described above and as represented in FIG. 5, each cache (e.g., 82_{T2}) includes various packet and error counts. At step 606, the current cache 82_{T2} is evaluated against a previous cache 82_{T0} having the same count information therein, although current interfaces may have been added or removed since the time T_0 . Note that if the cache 82_{T0} at time T_0 is too old or suspect, i.e., few if any of the interfaces are the same, the previous cache 82_{T0} can be scrapped, the current cache 82_{T2} can become the previous cache 82_{T0}, and after (possibly) a short delay, new current counts can be obtained which become the values in the current cache 82_{T2}. In any event, the values cached in the cache 82_{T2} are statistically evaluated against those in the cache 82_{T1} to determine if the network connectivity has changed.

In general, if an incoming packet count has increased from time T_2 to T_0 , and the errors are low, the network is alive, to a high degree of certainty. Conversely, if the outgoing packet counts have increased but the corresponding

incoming counts have not relatively increased, the network is likely not alive. For example, to determine network connectivity, if unicastIN and unicastOUT have changed, the network is considered to be alive. Also, if unicastIN and unicastOUT have both not changed, AND broadcastIN and non-unicastOUT have changed by different amounts, the network is considered to be alive. However, if broadcastIN and non-unicastOUT have changed by the same amounts, it is just broadcast activity (e.g., the network tap has probably been pulled out), whereby the network is considered to be not alive. Moreover, if the Errors IN/OUT or discards IN/OUT have changed, the network is most likely alive and is thus considered as such.

Once the state is determined, in the API call step 610 is executed to return the state as a result to the calling application. Step 612 is then executed to determine if the state has changed from its previous true or false value. If the state has changed, the SENS 60 fires the event, Network Alive (if True) or Network Not Alive (if false), to provide the current state via the Loosely Coupled Events database to the clients registered therefor. Lastly, at step 616, this current state is maintained as the previous state and the current cache as the previous cache to be available for the next evaluation.

In accordance with another aspect of the present invention, the SENS 60 also provides an event and/or API response as to whether a particular network destination is reachable. Applications can call the IsDestinationReachable() API or register for DestinationReachable change events. By way of example, rather than simply knowing whether the network is alive, an electronic mail program may want to know whether its mail server is reachable. To this end, the electronic mail program calls the IsDestinationReachable() API or registers (typically at installation time) with the Loosely Coupled Events database 70 for "DestinationReachable" notifications, and provides the name of the mail server. The Loosely Coupled Events database 70 then informs the SENS 60, whereby the SENS 60 will find out and thereafter monitor this destination. The SENS 60 then fires events when the state of the mail server switches from reachable to not reachable and vice-versa.

To determine destination reachability, the SENS 60 essentially executes the steps of FIG. 7, beginning at step 700 where a test is made as to whether the destination is named or is in the form of an IP address. If named, the SENS 60 attempts to resolve the name, i.e., by calling external TCP/IP name resolution APIs, and obtaining a result at step 702. If unable to be resolved, step 704 branches to step 706

where the "not reachable" result is returned to the calling program (if called as an API). A "Ping" cache 98 (FIG. 8) is updated at step 708 to reflect the unreachable state before branching to step 716, described below.

5 If the IP address is known, either at step 700 or via steps 702 - 704, step 710 then tests to determine if the IP address corresponds to a local subnet (known from the value of the address). If so, then the destination is automatically considered reachable, and the reachable result is returned to
10 the calling program (if called as an API) before branching to step 716, described below. Note that when a destination is considered reachable by the SENS 60, it is not a guarantee of reachability to an application. However local subnets are worth trying, and thus a "reachable" result is returned.

15 If the IP address does not correspond to a local Subnet, at step 710, the destination may be pinged (i.e., a packet sent thereto) to see if it responds, whereby it is known whether it is reachable. However, rather than ping each time, the ping cache 98 may be maintained that keeps the reachable /
20 unreachable states of one or more destinations therein. The ping cache 98 is regularly updated while the network is alive, for example, each destination in the ping cache 98 is pinged once every five minutes. The last pinged state for the appropriate destination is returned at step 714 to the

application calling the API, although as can be appreciated, alternatively the API call can force the ping.

Steps 716 and 718 cause an event to be fired to registered clients if a state change has occurred. For example, a name that previously was not resolvable is now resolved and it is in the local Subnet, or now responds when pinged, or a destination that formerly responded to pings no longer responds. Note that as also represented in FIG. 7, the ongoing monitoring process of the SENS 60 essentially pings each registered destination on a regular basis and then performs the steps 716 - 718 to determine whether to fire an event.

A simple way in which to ping destinations is to keep a list of destinations and their corresponding reachable or unreachable states in the ping cache 98 as shown in FIG. 8. Then, a thread unblocks and executes once every time period (e.g., five minutes), and loops through the list by pulling each destination off of the list and essentially executing the steps of FIG. 7 therefor, writing any changed result into the ping table 98. The thread then blocks until again needed.

However, while effective, the simple looping mechanism wastes a thread since most of the time the thread is idle while blocking. A more efficient way to perform the same pinging loop is to use thread pooling. In thread pooling,

each executable is assigned a number of threads $100_1 - 100_k$,
(e.g., three or four), plus a single thread (DLL) 102 which
maintains a timer queue 104 of timed work items, one-time
queued work items, and/or wait-based work items that wait on
5 an event. At present, this provides the ability to wait on
sixty-two objects with one thread 102. The SENS 60, using
thread-pooling APIs 106, registers each destination to ping as
a work item $102_1 - 102_i$ with the operating system, along with
any wait-based work items such as RAS connect and disconnect.
10 The single thread 102 allocates one or more worker threads
(e.g., 100_1) to work items $102_1 - 102_i$ in the queue 104 as
appropriate, i.e., once every time period for ping work items,
whereby the pinging operation takes place. When not pinging,
threads may be thus allocated to other processes rather than
15 blocking.

In accordance with another aspect of the present
invention, the SENS 60 provides notifications of AC and
battery power events reported by the operating system 35. The
ISensOnNow interface is implemented by clients interested in
20 any of the SENS power events. As described above, this
interface is an outgoing interface defined by SENS and
implemented by the subscriber application as a dispatch
interface. As also described above, when registering for
battery low notifications, clients can specify filtering

information. Each SENS power event corresponds to a method in the ISensOnNow interface, set forth below in Table 5:

Table 5

ISensOnNow Methods	Description
OnACPower	Switched to AC power.
OnBatteryPower	Switched to Battery power.
BatteryLow	Battery power is low.

5

Additional details for some of the methods of the

ISensOnNow interface are set forth below:

ISensOnNow::OnACPower

SENS calls this method to notify your application that the computer is using AC power.

HRESULT OnACPower(void);

Dispatch Identifier

[id(0x00000001)]

Return Values

S_OK

Method returned successfully.

Remarks

SENS calls this method to notify an application that AC power has been activated. If an application subscribes to this event, there are no filters to specify.

ISensOnNow::OnBatteryPower

SENS calls this method to notify an application that the computer is using battery power.

HRESULT OnBatteryPower(

 DWORD dwBatteryLifePercent // Percent of battery power remaining
);

Parameters

dwBatteryLifePercent

[in] Specifies the percent of battery power remaining.

Dispatch Identifier

[id(0x00000002)]

Return Values

S_OK

Method returned successfully.

Remarks

SENS calls this method to notify an application that the computer is using battery power. The remaining percentage of battery power is specified. If an application subscribes to this event, there are no filters to specify.

The SENS 60 also handles additional notifications related to various system states via the ISensLogon interface. If any clients are interested, the SENS 60 centrally registers to find out about these events with the operating system /

Winlogon service. The client application registers for these notifications and implements this ISensLogon interface as described above, whereby the SENS 60, via the Loosely Coupled Events database 70, calls the ISensLogon methods on the appropriately registered sink object to fire the corresponding event. The following table, Table 6, describes these events:

Table 6

ISensLogon Methods	Description
Logon	A user has logged on.
Logoff	A user has logged off.
StartShell	Shell has been started.
DisplayLock	Screen display has been locked.
DisplayUnlock	Screen display has been unlocked.
StartScreenSaver	Screen saver has been started.
StopScreenSaver	Screen saver has been stopped.

Lastly, the SENS 60 provides a special facility that may be used just before logoff, such as for synchronization purposes. As with logon, the SENS 60 registers with the operating system for certain event notifications. However,

rather than after the event starts, when the SENS 60 receives the logoff indication, the SENS 60 fires a logoff event (if a client is registered for notification) and then delays the logoff process until a client that has registered for logoff notification instructs the SENS 60 to continue. This allows a client to perform pre-logoff processing after the user has requested logoff but before the actual logoff operation occurs.

As can be seen from the foregoing detailed description, there is provided a centralized system event notification service that notifies registered clients of events. The method and system provide information such as network information that is otherwise unavailable or inconsistent in a consistent, efficient and extensible way.

While the invention is susceptible to various modifications and alternative constructions, a certain illustrated embodiment thereof is shown in the drawings and has been described above in detail. It should be understood, however, that there is no intention to limit the invention to the specific form or forms disclosed, but on the contrary, the intention is to cover all modifications, alternative constructions, and equivalents falling within the spirit and scope of the invention.

WHAT IS CLAIMED IS:

1. A system for providing notifications of computer system events to clients, comprising, a central service for receiving system events and for firing event notifications in response thereto, a registration mechanism for clients to register for notification of one or more types of events, and a distribution mechanism for communicating a fired event notification to each client registered for notification thereof based on the type of event notification.

2. The system of claim 1 wherein the registration mechanism and distribution mechanism are incorporated in a loosely coupled events database, and wherein the central service is a publisher and each client is a subscriber.

3. The system of claim 1 wherein the notification includes activating, starting or running a program or script.

4. The system of claim 1 wherein the client registers for notification for a type of event with the registration mechanism and includes condition information therewith, and the distribution mechanism includes a filtering mechanism for selectively communicating an event notification based on at least one condition.

5. The system of claim 3 wherein the registration mechanism and distribution mechanism are incorporated in a loosely coupled events database.

6. The system of claim 1 wherein the central service receives at least some of the system events from an operating system.

7. The system of claim 1 wherein the system event includes information related to the power state of the machine.

8. The system of claim 1 wherein the system event includes information related to the logon state of the machine.

9. The system of claim 1 wherein the central service receives system event information related to a network.

10. The system of claim 1 wherein the central service includes a plurality of time-based caches for caching network information, and a mechanism for evaluating the caches to determine a connectivity state of a network.

11. The system of claim 10 wherein the time-based caches maintain counts corresponding to network activity.

12. The system of claim 11 wherein the time-based counts corresponding to network activity include counts of incoming packets, outgoing packets, incoming errors and outgoing errors.

13. The system of claim 12 wherein the mechanism for evaluating the caches determines that the connectivity state of the network is true if the incoming packet counts have increased.

14. The system of claim 12 wherein the mechanism for evaluating the caches determines that the connectivity state of the network is false if the outgoing packet counts have increased and the incoming packet counts have not increased.

15. The system of claim 1 wherein the client includes a COM object, and the firing of an event results in a call to a method of the COM object.

16. The system of claim 15 wherein the COM object includes interfaces for receiving fired events.

17. The system of claim 16 wherein each interface for receiving fired events has at least one method accessible therethrough that corresponds to a type of event.

18. The system of claim 1 wherein the central service further includes a mechanism for determining whether a network destination is reachable.

19. The system of claim 18 wherein the mechanism for determining whether a network destination is reachable is associated with a list of network destinations.

20. The system of claim 19 wherein the mechanism for determining whether a network destination is reachable regularly polls each destination in the list to make a determination as to the reachability thereof.

21. The system of claim 20 wherein the mechanism for determining whether a network destination is reachable determines that a destination is not reachable if the name of

the destination is not resolvable into an Internet protocol address.

22. The system of claim 20 wherein the mechanism for determining whether a network destination is reachable determines that a destination is reachable if the Internet protocol address of the destination corresponds to a local subnet.

23. A computer-readable medium having computer-executable instructions for performing steps comprising:

- a) receiving system information at a central service;
- b) publishing an event notification in response thereto, the event notification having an event type associated therewith;
- c) receiving the event notification at a loosely coupled events database;
- d) matching the event notification with at least one client that has subscribed for event notification based on the type of event; and
- e) communicating the event notification to each client that has subscribed therefor.

24. The computer-readable medium of claim 23 having further computer-executable instructions for performing the step of, filtering event notifications by selectively communicating event notifications based on at least one condition.

25. The computer-readable medium of claim 23 wherein the central service receives the system information as system events from an operating system.

26. The computer-readable medium of claim 23 wherein the system information includes information related to a network.

27. The computer-readable medium of claim 26 wherein the network is a wide area network, and wherein the step of receiving system information at a central service comprises the step of receiving remote access services events.

28. The computer-readable medium of claim 26 wherein the network is a local area network, and having further computer-executable instructions for performing the step of caching network information corresponding to activity on the local area network.

29. The computer-readable medium of claim 28 having further computer-executable instructions for performing the step of evaluating cached network information to determine the state of network connectivity.

30. The computer-readable medium of claim 29 wherein the central service publishes an event when the state of network connectivity has changed from a previous value thereof.

31. The computer-readable medium of claim 29 wherein the client includes a COM object, and wherein the step of communicating the event notification to each client comprises the step of calling a method of the COM object.

32. The computer-readable medium of claim 23 having further computer-executable instructions for performing the step of determining whether a network destination is reachable.

33. The computer-readable medium of claim 32 wherein the central service publishes an event when the network destination changes from reachable to unreachable.

34. The computer-readable medium of claim 32 wherein the central service publishes an event when the network destination changes from unreachable to reachable.

35. The computer-readable medium of claim 32 wherein the step of determining whether the network destination is reachable comprises the step of pinging the destination.

36. The computer-readable medium of claim 32 wherein the step of determining whether the network destination is reachable comprises the step of periodically pinging the destination.

37. A method for providing information on a state of network connectivity, comprising the steps of, maintaining values indicative of network activity at a first time, obtaining values indicative of network activity at a second time, evaluating the differences between the values at the first time and the second time to determine the state of network connectivity, and selectively outputting the state of network connectivity.

38. The method of claim 37 wherein the step of evaluating the differences between the values at the first

time and the second time comprises the step of determining a number of incoming packet counts over a period of time.

39. The method of claim 37 wherein the step of evaluating the differences between the values at the first time and the second time comprises the step of determining a number of outgoing packet counts over a period of time.

40. The method of claim 37 wherein the step of evaluating the differences between the values at the first time and the second time comprises the step of determining a number of errors over a period of time.

41. The method of claim 37 wherein the step of evaluating the differences between the values at the first time and the second time comprises the step of determining a number of outgoing packet counts over a period of time relative to a number of incoming packet counts over a period of time.

42. The method of claim 37 wherein the step of selectively outputting the state of network connectivity comprises the step of firing an event when the state of

network connectivity has changed from a previous value thereof.

43. The method of claim 37 wherein the step of selectively outputting the state of network connectivity comprises the step of returning the state of network connectivity as a result in response to a call from a client.

ABSTRACT OF THE INVENTION

A method and system for providing system event notifications to clients such as applications. Clients register for notification of one or more types of events with a registration mechanism, and a System Event Notification Service, (SENS), receives system event information and fires event notifications in response thereto. A distribution mechanism selectively communicates the fired event to each client registered for notification thereof based on the type of event. Events include network events, for which the service monitors the connectivity state of the machine, including whether a connection is established or lost, the type of connection (LAN / WAN) and bandwidth information. To monitor a LAN state, the service caches outgoing and incoming network information including errors and packet counts and statistically evaluates this cached information against current information to determine whether the connection is established or lost. The service also determines if a destination (IP address or name) is reachable, by periodically polling destinations. Other system event notifications may be fired, including logon or logoff operations and power management events.




FIG. 2




FIG. 3




FIG. 4

82T2

Interface Number	a) Incoming Packet Count (non-Unicast)	b) Outgoing Packet Count (Unicast)	c) Incoming Errors	d) Outgoing Errors	e) Incoming Packet Count (non-Unicast)	f) Outgoing Packet Count (Unicast)
2	1200	26	360	4	1660	84
6	900	22	65	2	2123	67
5	790	19	44	2	868	445
0	311	14	3	1	199	378
LAN Cache						

FIG. 5

FIG. 6





FIG. 7



663220" 429990

Reachability Status	Dest.
Y	FOO
N	BAR
Y	WXYZ
Y	ABC
⋮	
Y	PQRYZ

FIG. 8




FIG. 9

COMBINED DECLARATION AND POWER OF ATTORNEY

As a below named inventor, I hereby declare that

My residence, post office address, and citizenship are as stated below next to my name.

I believe I am the original, first, and sole inventor (if only one name is listed below) or an original, first, and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled: "**System Event Notification Service**," the specification of which is attached hereto unless the following box is checked:

☐ was filed on _____ as United States Application Serial No. _____ or PCT International Application No. _____ and was amended on _____ (if applicable).

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to patentability as defined in 37 C.F.R. § 1.56.

I hereby claim foreign priority benefits under 35 U.S.C. § 119(a)-(d) or § 365(b) of any foreign application(s) for patent or inventor's certificate, or § 365(a) of any PCT international application which designated at least one country other than the United States of America, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate, or PCT international application having a filing date before that of the application on which priority is claimed.

Prior Foreign Application(s)

Priority Not Claimed

(Number) (Country) (Day/Month/Year Filed) ☐

(Number) (Country) (Day/Month/Year Filed) ☐

I hereby claim the benefit under 35 U.S.C. § 119(e) of any United States provisional application(s) listed below.

(Application Number) (Filing Date)

(Application Number) (Filing Date)

I hereby claim the benefit under 35 U.S.C. § 120 of any United States application(s), or § 365(c) of any PCT international application(s) designating the United States of America, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application(s) in the manner provided by the first paragraph of 35 U.S.C. § 112, I acknowledge the duty to disclose information which is material to patentability as defined in 37 C.F.R. § 1.56 which became available between the filing date of the prior application(s) and the national or PCT international filing date of this application.

(Application Number) (Filing Date) (Status – patented, pending, abandoned)

(Application Number) (Filing Date) (Status – patented, pending, abandoned)

As a named inventor, I hereby appoint the following attorneys to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith:

Albert S. Michalik, Reg. 37,395; Daniel D. Crouse, Reg. No. 32,022; Katie E. Sako, Reg. No. 32,628.

Address all telephone calls to Albert S. Michalik at telephone number (425) 836-3030.

Address all correspondence to The Law Offices of Albert S. Michalik
704 - 228th Avenue NE
Suite 193
Redmond, WA 98053

I hereby declare that all statements made herein of my own knowledge are true, that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Full name of **sole or first inventor**: Gopal Parupudi

Inventor's signature _____

Date Feb 22nd 1999

Country of Citizenship: India

Residence: 4221 255th Place SE, Issaquah Washington 98029

Post Office Address: Same

Full name of **second joint inventor**, if any: Mario C. Goertzel

Inventor's signature _____

Date 2/22/99

Country of Citizenship: USA

Residence: 12631 NE 107th Place, Kirkland, Washington 98033

Post Office Address: Same

Full name of **third joint inventor**, if any: Murthy Srinivas

Inventor's signature _____

Date 2/22/99

Country of Citizenship: USA

Residence: 9611 213th Avenue NE, Redmond, Washington 98053

Post Office Address: Same



Additional inventors are being named on separately numbered sheets attached hereto.
1630 declaration